

On the End-to-end Call Acceptance and the Possibility of Deterministic QoS Guarantees in Ad hoc Wireless Networks*

S. Sriram
Dept. of Computer Science
University of California, Berkeley, CA 94720
sriram_s@cs.berkeley.edu

B. S. Manoj
CallT2, Jacobs School of Engineering
University of California, San Diego, CA 92093
bsmanoj@ucsd.edu

T. Bheemarjuna Reddy
Dept. of Computer Science and Engineering
Indian Institute of Technology Madras, India
arjun@cs.iitm.ernet.in

C. Siva Ram Murthy†
Dept. of Computer Science and Engineering
Indian Institute of Technology Madras, India
murthy@iitm.ac.in

ABSTRACT

The issue of providing Quality of Service (QoS) guarantees in an Ad hoc wireless network is a very challenging problem. In this paper, we make the following contributions: (i) analytically derive bounds for the end-to-end call acceptance rate using existing queueing theory methods, (ii) study the impact of the routing scheme on the end-to-end call acceptance rate, and (iii) propose a differentiated services scheme for deterministically providing QoS guarantees.

Unlike existing studies which analyze the transport capacity, we focus on the end-to-end call acceptance. The framework that we assume is that of a TDMA-based Ad hoc wireless network. The routing scheme employed influences the end-to-end call acceptance of the network. The metrics that we consider are the call acceptance probability and the system saturation probability (*i.e.*, the probability that the network is in a state in which every new call is rejected). We derive general bounds on the call acceptance and the system saturation for the case of differentiated-classes of users in the network. These bounds indicate the number of calls of the highest priority class that can be admitted into the network.

Simulation studies were carried out to study the effect of load, hopcount, and the influence of the routing protocol on the call acceptance. The increase in the call acceptance rate with the introduction of load-balancing highlights the importance of load-balancing in enhancing the system performance. From these studies, we arrive at the following results: (i) load-balancing leads to significant

*This work was supported by iNautix Technologies India Private Limited, Chennai, India, Department of Science and Technology, New Delhi, India, and Microsoft Research University Relations India (Award Number 12715).

† Author for correspondence

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

MobiHoc'05, May 25–27, 2005, Urbana-Champaign, Illinois, USA.
Copyright 2005 ACM 1-59593-004-3/05/0005 ...\$5.00.

improvement in the end-to-end call acceptance rate, and is an important factor in attaining the maximum end-to-end call acceptance rate in a given network and (ii) it is indeed possible to provide deterministic QoS guarantees for a designated set of nodes which are characterized by “deterministic guarantee limit”.

Categories and Subject Descriptors: C.2.1 [Network Architecture and Design] Wireless communication; C.2.2 [Network Protocols] Routing protocols; C.4 [Performance of Systems] Modeling techniques, Performance attributes

General Terms: Algorithms, Theory, Performance

Keywords: Ad hoc wireless networks, QoS guarantees. QoS routing, TDMA, call acceptance rate, load-balancing, Markov process

1. INTRODUCTION

An Ad hoc wireless network is a collection of mobile nodes that can communicate over radio without any pre-existing infrastructure. Two nodes can communicate directly with each other if each lies in the transmission range of the other. Two nodes that cannot directly communicate can do so in a multi-hop manner in which the other nodes function as routers. Such networks are used in military installations and in emergency situations as they permit the establishment of a communication network at very short notice. However, these networks are limited by constraints in their bandwidth and power consumption.

With their widespread deployment, Ad hoc networks now need to support applications that generate real-time traffic. Such traffic requires the network to provide guarantees on the QoS of the connection. The important aspects in the process of providing such guarantees are the routing protocols that establish paths that can satisfy the QoS requirements and the reservation mechanisms that reserve the necessary resources along the path. A problem of considerable interest in this regard is that of theoretically estimating the nature of the guarantees that can be provided by a QoS scheme. These estimates on the parameters of QoS routing protocols give us an idea of the maximum guarantees that can be provided, and allow us to gauge how far the existing schemes are from the ideal limit.

In this work, we consider the problem of QoS routing in a TDMA-based Ad hoc wireless network, where the QoS constraint on the calls is that of bandwidth. Our focus is the **end-to-end call accep-**

tance rate which is a measure of the number of calls that can be admitted into the network. The calls arriving in the network belong to different classes based on which the requirements of the calls are prioritized. Thus, the parameters that we focus on are: the call acceptance probability and the system saturation probability. The variation of these parameters enables us to answer questions such as 1) What are the maximum number of high-priority calls that can be sustained in the network at a given load?, 2) What is the likelihood that the network enters a state where no more new calls can be accepted?, 3) What is the effect of the routing protocol on the call acceptance?, 4) How close to the theoretical limit do the routing protocols approach? Then, we address the problem of ensuring deterministic call acceptance for a certain sub-set of the calls. We estimate the **deterministic guarantee limit** which is a mobility-independent measure of the number of high-priority calls that can be admitted into the network. We also determine the call acceptance probability for the classes for which deterministic guarantee cannot be provided.

In this work, we model the network at the level of the transmission range of each node. The range of a node is analyzed as a Markov process where the calls are the entities to be serviced. The reservation of slots for the call in the transmission range constitutes the service of the call. The modeling of a wireless network as a collection of Markov processes is unique in that, due to the local broadcast nature of the channel, the reservation of slots in the transmission range of a node affects the status of the slots in the neighboring regions. Capturing this property of wireless networks is essential to model the characteristics of the network accurately. Such a modeling must also be able to reflect the characteristics of the routing protocol used. We begin by analyzing a general case of a network that can support multiple-classes of calls where preemption of calls does not exist. We then provide a closed-form estimate of the call acceptance probability and the saturation probability for the case of a single-class of users and discuss the probabilities for the highest-priority class in the preemptive case. We compare the call acceptance probabilities of shortest-path routing and two routing protocols that attempt load-balancing. Finally, we estimate the deterministic guarantee limit.

The rest of this paper is organized as follows: Section 2 briefs the related work in this area, Section 3 describes our work, Section 4 discusses the details of the simulation, and Section 5 presents the simulation results. Finally Section 6 concludes the paper.

2. RELATED WORK

In their seminal work[1], Gupta and Kumar introduced a random network model for studying throughput scaling in a fixed wireless network. They showed that even under optimal conditions, the transport capacity (bit-distance product that can be transmitted over the network) of the network is $\theta(\sqrt{n})$ bit-meters/s, where n is the number of nodes present in the network, for the protocol model considered. In [2] an information-theoretic scheme was constructed for obtaining an achievable rate region in a network of arbitrary size and topology. The proposed scheme allows a feasible transport capacity of $\theta(n)$ bit-meters/s in a specific wireless network of nodes located in a region of unit area, as compared to $\theta(\sqrt{n})$ bit-meters/s obtained in [1] for less sophisticated receiver operation.

In [3], the authors showed that by allowing nodes to move, the throughput scaling changes dramatically. They showed that if node motion is independent across nodes and has a uniform stationary distribution, a constant throughput scaling ($\theta(1)$) per source - destination pair is feasible. In [4], the authors studied the transport capacity of an Ad hoc wireless network overlaid with an infinite capacity infrastructure network.

While the previous studies analyze the transport capacity of Ad hoc networks, in this work our focus is on the **end-to-end call acceptance rate** which is a measure of the number of calls with end-to-end bandwidth reservation that can be supported by the network. The previous studies on transport capacity study how it scales with the number of nodes. We study the dependence of end-to-end call acceptance rate on the network load and the routing protocol. Our work attempts to arrive at generalized bounds that can be used to analyze routing protocols. A number of QoS routing protocols have been proposed for Ad hoc wireless networks (for more details, refer [5], [6], [7], and [8]). The framework that we assume is that of a TDMA-based network. The routing scheme employed influences the end-to-end call acceptance rate of the network. In this paper, we investigate the end-to-end call acceptance rate and the influence of shortest-path routing and load-balanced routing protocols on it.

3. OUR WORK

We consider an Ad hoc wireless network comprising N nodes uniformly distributed at random in a terrain of area A . The transmission range of each node is R . We assume the presence of a slotted TDMA mechanism at the MAC layer. The total number of slots available in the network is B . However, it is possible to reuse the slots spatially depending on the interference pattern of the nodes. This is the key idea that is used in deriving the bounds.

The bandwidth of a call is measured in terms of the number of slots used for transmission. A call is setup by reserving slots along the path of the call. A node may either transmit or receive in a particular slot (a node is said to receive in a particular slot if any of its neighbors is transmitting in that slot). A slot is said to be free at a node j , ($1 \leq j \leq N$) if it is neither transmitting nor receiving during that slot. For a node j to transmit in a particular slot, the slot must be free at j and none of the neighbors of j must be receiving in that slot. For a node j to receive in a particular slot, the slot must be free at j . This definition permits node 6 to transmit to node 5 in the same slot as the one used by node 1 to transmit to node 2 in Figure 1, provided nodes 1 and 2 do not hear 6. On the other hand, in the sender's range, node 4 must use a different slot to transmit to node 3 because node 3 hears the transmission by node 1.




Figure 1: An example of possible transmissions.

3.1 System Model

Consider a network of $NW = \{1, \dots, N\}$ of N nodes that can support K classes of calls where class i calls have a higher priority

than class j ($1 \leq i < j \leq K$) calls. We would like an estimate of how many calls of a particular class can be supported. This implies that we can definitely support such a number of class 1 calls where class 1 is the highest priority class. If all the available slots are occupied by calls of various classes upon arrival of a class j call, one or more calls of lower priority classes can be preempted based on the bandwidth requirement of class j call that has arrived to ensure that the arrived call be accepted. Thus, we would like to provide a guarantee on the number of calls of a particular class that can be accepted.




Figure 2: An example scenario.

Assumptions made for the analysis are the following:

- Calls of a particular class- k arrive at each node distributed according to a *Poisson* process of mean λ_k .
- The duration of a call is exponentially distributed with mean duration $\frac{1}{\mu_k}$.
- We assume that the calls of all classes have equal bandwidth requirements: each call requires a single slot.
- We do not take node mobility into account in the estimation of call acceptance and system saturation. (However, the deterministic guarantee limit is *independent* of mobility.)
- We assume that the routing algorithm is such that for any path found by the algorithm, the number of nodes on the path that lie within the transmission range of any node on the path (inclusive of the node itself) is not greater than some constant c . In the absence of such an assumption, it is possible to construct a scenario (Figure 2) where a single call needs to use all the slots in the system. In Figure 2, each of the nodes on the path is in the transmission range of the other nodes. So the use of a slot for transmission by one of the nodes implies that the slot cannot be re-used by the other nodes on the path. Thus, if node A_1 transmits to node A_2 on slot #1, slot #1 cannot be used by any of the other nodes to transmit to their downstream nodes. If we were to consider a P -hop path with the nodes in the configuration given in Figure 2, the number of slots used would be P . Hence, it would be difficult to provide a bound on the number of calls that can be admitted. This property is satisfied with $c = 3$ for protocols that ensure that if a path is to be set up from A_1 to A_3 , the path used is the link (A_1, A_3) rather than links (A_1, A_2) and (A_2, A_3) ,




Figure 3: An example to distinguish free slots at a node and free slots in a region.

where A_1 , A_2 , and A_3 are nodes such that each can listen to the other two. This can be done by using an appropriate forwarding of the route request packets in which a node drops all except the first route request that it receives.

3.2 Theoretical Analysis

Initially, we assume that call preemption does not occur. We derive upper and lower bounds on the call acceptance probability for the case of single-hop and multi-hop calls, respectively. Consider a node j and the region spanned by its transmission range $R(j)$. Any call passing through $R(j)$ uses up some number of slots. The number of slots used up in the region $R(j)$ depends on the number of calls originated from node j , the number of calls from any of the neighbors of node j , and the number of calls that originate from outside $R(j)$ and are routed through $R(j)$. A slot is said to be **free** in $R(j)$ if no nodes in $R(j)$ are either transmitting or receiving in that slot (*i.e.*, slot is free at all nodes in region $R(j)$). In Figure 3, node A_1 transmits to node A_2 on slot 1. Node A_4 transmits to node A_2 on slot 2. Node A_5 transmits to node A_3 on slot 3. If the network had a total of 5 slots, the free slots at node A_1 would be $\{2, 3, 4, 5\}$ while the free slots in the region $R(A_1)$ would be $\{4, 5\}$. We can thus view $R(j)$ as a server of slots for which the calls contend. Although the distribution of call arrivals of a particular class at each node is known to be *Poisson*, the distribution of calls arriving at $R(j)$ is not *Poisson* due to the splitting of the *Poisson* streams (Consider calls arriving at a node based on a *Poisson* process of mean λ . Assume that the node has to forward the call along one of two links. If the node forwards calls in a non-random manner, the arrival of calls at the downstream node will no longer be *Poisson*). We make use of Kleinrock's Independence Assumption, according to which, for moderately heavy call arrival at each node, the net call arrival at the region $R(j)$ can be regarded as *Poisson*. Thus, calls of a class- k arrive at $R(j)$ according to a *Poisson* distribution with mean:

$$\lambda_k(j) = \sum_{i=1}^{i=N} f_k(i, j) \lambda_k$$

where $f_k(i, j)$ is the fraction of class- k calls originating in node i that pass through the region $R(j)$. This can be rewritten as:

$$\lambda_k(j) = \left(\sum_{i \notin R(j)} f_k(i, j) + |N(j)| + 1 \right) \lambda_k \quad (1)$$




Figure 4: The transitions into and out of one of the states of the Markov process representing the region $R(j)$. For the state (n_1, n_2, \dots, n_K) , $n_1 > 0, n_2 > 0, \dots, n_K > 0$.

where $N(j)$ denotes the set of nodes in the transmission range of node j . The parameter $f_k(i, j)$ is **dependent** on the routing protocol. For a protocol such as shortest-path routing, which leads to heavy loads in the center of the network, $f_k(i, j)$ would be high for nodes j ($1 \leq j \leq N$) located near the center. For protocols that implement load-balancing, the value of $f_k(i, j)$ should be fairly uniform across the nodes.

The state of the system $R(j)$ is given by the number of calls of each class being served (each of which uses up some of the slots of $R(j)$) by $R(j)$. We thus model $R(j)$ as a K -dimensional discrete-time Markov process¹ $X(t) = (n_1, \dots, n_K)$, where n_k denotes the number of class- k calls being served by $R(j)$ at time t [11].

We denote: $P((n'_1, \dots, n'_K)|(n_1, \dots, n_K)) = P(X(t + \Delta t) = (n'_1, \dots, n'_K)|X(t) = (n_1, \dots, n_K))$ as the probability that the system $R(j)$ is in the state (n'_1, \dots, n'_K) at time $t + \Delta t$ given it is in the state (n_1, \dots, n_K) at time t .

$$P((n_1, \dots, n_k + 1, \dots, n_K)|(n_1, \dots, n_k, \dots, n_K)) = \lambda_k(j)\Delta t \quad (2)$$

$$P((n_1, \dots, n_k - 1, \dots, n_K)|(n_1, \dots, n_k, \dots, n_K)) = n_k \mu_k \Delta t, \quad n_k > 0 \quad (3)$$

The state-transition diagram representing the transitions into and out of one of the states of the Markov process is shown in Figure 4.²

The Markov process has a unique steady-state probability distribution [11]. Using Equations (2) and (3) along with the normalization of probabilities, we can calculate the probability that the

¹In the most general case of a model corresponding to K classes of calls, the Markov process has $\binom{K+B}{B}$ states. This is not a problem for the current analysis since the transitions between the states are restricted: every state has at most $2K$ neighboring states, and the processes associated with any given regions are decoupled. Further, we are interested in only the steady state of the process and not in the paths traversed. The state-explosion needs to be tackled for an analysis that considers coupled processes or preemptive calls: the interested reader may refer [9] and [10].

²For the case of preemption, the system can move between certain other states. Corresponding to the case of preemption of a class-2 call by a class-1 call, the system can move from the state (n_1, n_2, \dots, n_K) to $(n_1 + 1, n_2 - 1, \dots, n_K)$, $n_2 \geq 1$.

system is in a particular state (n_1, \dots, n_K) as:

$$P((n_1, \dots, n_K)) = \frac{1}{G(j)} \prod_{k=1}^{k=K} \frac{\rho_k(j)^{n_k}}{n_k!} \quad (4)$$

where $\rho_k(j) = \frac{\lambda_k(j)}{\mu_k}$ and

$$G(j) = \sum_{0 \leq n_1 + \dots + n_K \leq B} \prod_{k=1}^{k=K} \frac{\rho_k(j)^{n_k}}{n_k!}$$
 is a normalization factor.

We would now like to extend this Markov process to distinguish between calls that terminate in a node in $R(j)$ (call them type-U calls) and those that do not (type-V calls). Let us say that a fraction f of the calls terminate in some node in $R(j)$. If the destination were to be chosen randomly, then $f = \frac{|N(j)|+1}{N}$. The state of the system is now given by:

$$(n_{1,U}, n_{1,V}, n_{2,U}, n_{2,V}, \dots, n_{K,U}, n_{K,V})$$

where $n_{k,U}$ is the number of class- k calls that are type-U calls in $R(j)$ and $n_{k,V}$ is the number of class- k calls that are type-V calls. The probability that the system is in a state $(n_{1,U}, n_{1,V}, n_{2,U}, n_{2,V}, \dots, n_{K,U}, n_{K,V})$ is:

$$P((n_{1,U}, n_{1,V}, \dots, n_{K,U}, n_{K,V})) = \frac{1}{E(j)} \prod_{k=1}^{k=K} \frac{\rho_{k,U}(j)^{n_{k,U}} \rho_{k,V}(j)^{n_{k,V}}}{n_{k,U}! n_{k,V}!} \quad (5)$$

where $\rho_{k,U}(j) = \frac{f \lambda_k(j)}{\mu_k}$, $\rho_{k,V}(j) = \frac{(1-f) \lambda_k(j)}{\mu_k}$, and

$$E(j) = \sum_{n_{1,U}, n_{1,V}, \dots, n_{K,U}, n_{K,V}} \prod_{k=1}^{k=K} \frac{\rho_{k,U}(j)^{n_{k,U}} \rho_{k,V}(j)^{n_{k,V}}}{n_{k,U}! n_{k,V}!}$$
 is a normalization factor.

The probability that the system is in a state $(n_{1,V}, n_{2,V}, \dots, n_{K,V})$ (a state in which there are $n_{1,V}$ class-1 type-V calls, $n_{2,V}$ class-2 type-V calls, and so on) is:

$$P((n_{1,V}, \dots, n_{K,V})) = \frac{1}{H(j)} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(j)^{n_{k,V}}}{n_{k,V}!} \quad (6)$$

where $H(j) = \sum_{0 \leq n_{1,V} + \dots + n_{K,V} \leq B} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(j)^{n_{k,V}}}{n_{k,V}!}$ is a normalization factor.




Figure 5: In the region $R(j)$, C1 and C4 are type-U calls; C2, C3, and C5 are type-V calls. For each type-V call, we see that at least one slot that has not been used so far in $R(j)$ must be used. For the type-U calls, slot reuse is possible in some cases.

3.2.1 Call Acceptance Probability

In this section, we are going to derive the call acceptance probability of both single-hop and multi-hop cases for a non-preemptive system (a system where the accepted calls are not dropped for a new call).

LEMMA 1. $P(\text{Number of used slots in a region } R(j) \leq x) \leq P(\text{Number of type - V calls in } R(j) \leq x)$, where $x \in \mathbb{N}$.

Proof: For every type-V call, at least one unique (until then unused) free slot in the region $R(j)$ must be used (see Figure 5). Thus:

$$\begin{aligned} \text{Number of type - V calls in } R(j) > x &\Rightarrow \\ \text{Number of used slots in } R(j) > x & \\ \text{and} & \\ \text{Number of used slots in } R(j) \leq x &\Rightarrow \\ \text{Number of type - V calls in } R(j) \leq x & \end{aligned}$$

$$\begin{aligned} \text{Hence } P(\text{Number of used slots in } R(j) \leq x) &\leq \\ P(\text{Number of type - V calls in } R(j) \leq x) & \end{aligned}$$

□

LEMMA 2. $P(\text{Number of calls in a region } R(j) \leq x) \leq P(\text{Number of used slots in a region } R(j) \leq cx)$, where $x \in \mathbb{N}$ and c is the routing - algorithm dependent constant factor that denotes the maximum number of nodes on a path that lie within the transmission range of any node on the path.

Proof:

$$\begin{aligned} \text{Number of calls in } R(j) \leq x &\Rightarrow \\ \text{Number of used slots in } R(j) \leq cx & \end{aligned}$$

$$\begin{aligned} \text{Hence } P(\text{Number of calls in } R(j) \leq x) &\leq \\ P(\text{Number of used slots in } R(j) \leq cx) & \end{aligned}$$

□

Theoretical upper bound for probability of call acceptance

We now derive an upper bound on the probability of call acceptance for the cases of single-hop and multi-hop calls.

Single-hop case: Consider a single-hop call from node j to its neighbor node l . For the call to be accepted, at least one slot must be free in the region $R(j)$. Thus P_{Acc} (probability of a single-hop call is accepted) is:

$$\begin{aligned} P_{Acc} &= P(\text{Number of free slots} \geq 1) \\ &= P(\text{Number of used slots} \leq B - 1) \end{aligned}$$

where B is the total number of slots in the system. From Lemma 1:

$$\begin{aligned} P_{Acc} &\leq P(\text{Number of type - V calls} \leq B - 1) \\ &\leq 1 - P(\text{Number of type - V calls} > B - 1) \\ &\leq 1 - P(\text{Number of type - V calls} = B) \end{aligned}$$

$$P_{Acc} \leq 1 - \sum_{n_{1,V} + n_{2,V} + \dots + n_{K,V} = B} \frac{1}{H(j)} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(j)^{n_{k,V}}}{n_{k,V}!} \quad (7)$$

For the case of a single-class of calls, Equation (7) reduces to

$$P_{Acc} \leq 1 - \frac{1}{H(j)} \frac{\rho_{1,V}(j)^B}{B!} \quad (8)$$

Multi-hop case: We set the constant $c = 3$. Consider a $(M - 1)$ -hop call ($M \geq 3$) setup along the nodes (p_1, \dots, p_M) . When a slot is reserved for transmission between p_1 and p_2 , the total number of free slots at $R(p_2)$ decreases by 1 (since the slot cannot be used for transmission from p_2 to p_3). Thus, the total number of slots available at $R(p_2)$ can be considered as $B - 1$. Call this modified region $R'(p_2)$. When slots have been reserved between p_1 and p_2 , and between p_2 and p_3 , the number of free slots at $R(p_3)$ decreases by 2 so that the total number of slots at $R(p_3)$ can be regarded as $B - 2$. Call this modified region $R''(p_3)$. The number of slots, for the regions $R(p_3), \dots, R(p_{M-1})$, is thus effectively, $B - 2$ (since $c = 3$). (Thus, according to this notation, a region $R'(j)$ has one fewer slot, while $R''(j)$ has two fewer slots). A multi-hop call setup for $M = 5$ is shown in Figure 6.

A call is **successfully forwarded** in region $R(j)$ if slots can be found in $R(j)$ so that the call having arrived at node j is forwarded to its next hop in the path. For the call to be accepted, it must first be successfully forwarded in the region $R(p_1)$, must then be successfully forwarded through each of the regions $R'(p_2), R''(p_3), \dots$,




Figure 6: Multi-hop call setup. $R(P_1)$ needs slot #1 to be free. $R(P_2)$ now cannot use slot #1 and requires slot #2 (some other slot) to be free. $R(P_3)$ cannot use slots #1 and #2, and requires slot #3 (any other slot) to be free. $R(P_4)$ can transmit in slot #1 if it is free.

$R''(p_{M-1})$. A necessary and sufficient condition for successful forwarding is the presence of at least one free slot in each of the intermediate regions.

Denote: Successful forwarding of call in $R(j)$ as SF of call in $R(j)$. Thus P_{Acc} is given by:

$$\begin{aligned}
P_{Acc} &= P(\text{SF of call in } R(p_1)) \times \\
&P(\text{SF of call in } R'(p_2) | \text{SF of call in } R(p_1)) \times \\
&P(\text{SF of call in } R''(p_3) | \text{SF of call in } R'(p_2)) \times \\
&\dots \\
&P(\text{SF of call in } R''(p_{M-1}) | \text{SF of call in } R''(p_{M-2})) \\
P_{Acc} &= P(\text{No. of free slots in } R(p_1) \geq 1) \times \\
&P(\text{No. of free slots in } R'(p_2) \geq 1 | \text{SF of call in } R(p_1)) \times \\
&P(\text{No. of free slots in } R''(p_3) \geq 1 | \text{SF of call in } R'(p_2)) \times \\
&\dots \\
&P(\text{No. of free slots in } R''(p_{M-1}) \geq 1 | \text{SF of call in } R''(p_{M-2})) \quad (9)
\end{aligned}$$

From Lemma 1:

$$\begin{aligned}
P_{Acc} &\leq P(\text{No. of type - V calls in } R(p_1) \leq B-1) \times \\
&P(\text{No. of type - V calls in } R'(p_2) \leq B-2) \times \\
&P(\text{No. of type - V calls in } R''(p_3) \leq B-3) \times \\
&\dots \\
&P(\text{No. of type - V calls in } R''(p_{M-1}) \leq B-3)
\end{aligned}$$

$$\begin{aligned}
P_{Acc} &\leq \left(1 - \frac{1}{\sum_{n_1, V+n_2, V+\dots+n_K, V=B} \frac{1}{H(p_1)} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(p_1)^{n_{k,V}}}{n_{k,V}!}} \right) \times \\
&\left(1 - \frac{1}{\sum_{n_1, V+n_2, V+\dots+n_K, V=B-1} \frac{1}{H'(p_2)} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(p_2)^{n_{k,V}}}{n_{k,V}!}} \right) \times \\
&\left(1 - \frac{1}{\sum_{n_1, V+n_2, V+\dots+n_K, V=B-2} \frac{1}{H''(p_3)} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(p_3)^{n_{k,V}}}{n_{k,V}!}} \right) \times \\
&\dots \\
&\left(1 - \frac{1}{\sum_{n_1, V+n_2, V+\dots+n_K, V=B-2} \frac{1}{H''(p_{M-2})} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(p_{M-2})^{n_{k,V}}}{n_{k,V}!}} \right) \times \\
&\left(1 - \frac{1}{\sum_{n_1, V+n_2, V+\dots+n_K, V=B-2} \frac{1}{H''(p_{M-1})} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(p_{M-1})^{n_{k,V}}}{n_{k,V}!}} \right) \quad (10)
\end{aligned}$$

$$\text{where } H'(j) = \sum_{0 \leq n_1, V+\dots+n_K, V \leq B-1} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(j)^{n_{k,V}}}{n_{k,V}!} \text{ and}$$

$$H''(j) = \sum_{0 \leq n_1, V+\dots+n_K, V \leq B-2} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(j)^{n_{k,V}}}{n_{k,V}!}.$$

For the case of a single-class of calls, Equation (10) reduces to

$$\begin{aligned}
P_{Acc} &\leq \left[1 - \frac{1}{H(p_1)} \frac{\rho_{1,V}(p_1)^B}{B!} \right] \times \\
&\left[1 - \frac{1}{H'(p_2)} \frac{\rho_{1,V}(p_2)^{B-1}}{(B-1)!} \right] \times \\
&\left[1 - \frac{1}{H''(p_3)} \frac{\rho_{1,V}(p_3)^{B-2}}{(B-2)!} \right] \times \\
&\dots \\
&\left[1 - \frac{1}{H''(p_{M-2})} \frac{\rho_{1,V}(p_{M-2})^{B-2}}{(B-2)!} \right] \times \\
&\left[1 - \frac{1}{H''(p_{M-1})} \frac{\rho_{1,V}(p_{M-1})^{B-2}}{(B-2)!} \right] \quad (11)
\end{aligned}$$

The RHS (Right Hand Side) of Equations (8) and (11) are hard to solve for in a closed-form. For moderate-to-heavy traffic, $\rho > 1$

and the inequality remains valid if we replace $\rho_{1,V}(p_j)$, $1 \leq j \leq M-1$ by $\rho_{1,V}^{Max}$ (the maximum value of $\rho_{1,V}(p_j)$ across all the regions). Denoting the RHS as P_{Acc}^{Max} :

$$P_{Acc}^{Max} = 1 - \frac{1}{H} \frac{\rho_{1,V}^{Max B}}{B!} \text{ for single-hop calls} \quad (12)$$

$$\begin{aligned}
P_{Acc}^{Max} &= \left[1 - \frac{1}{H} \frac{\rho_{1,V}^{Max B}}{B!} \right] \times \left[1 - \frac{1}{H'} \frac{\rho_{1,V}^{Max B-1}}{(B-1)!} \right] \times \\
&\left[1 - \frac{1}{H''} \frac{\rho_{1,V}^{Max B-2}}{(B-2)!} \right]^{M-3} \text{ for multi-hop calls} \quad (13)
\end{aligned}$$

$$\text{where } H = \sum_{b=0}^{b=B} \frac{\rho_{1,V}^{Max b}}{b!}, \text{ and } H' = \sum_{b=0}^{b=B-1} \frac{\rho_{1,V}^{Max b}}{b!}, \text{ and } H'' = \sum_{b=0}^{b=B-2} \frac{\rho_{1,V}^{Max b}}{b!}.$$

Theoretical lower bound for probability of call acceptance

In this section, we derive lower bounds on the probability of call acceptance for the case of single-hop and multi-hop calls.

Single-hop case: For the single-hop case, a call from node j to its neighbor node l is accepted if there is at least one free slot in the region $R(j)$. From our assumption about the fact that the routing protocol satisfies the property that at most c nodes on the path can hear any other node on the path, we have for a given number of calls in the region $R(j)$

$$\begin{aligned}
P_{Acc} &= P(\text{Number of free slots} \geq 1) \\
&= P(\text{Number of used slots} \leq B-1) \quad (14)
\end{aligned}$$

Using Lemma 2

$$\begin{aligned}
P_{Acc} &\geq P(\text{Number of calls} \leq \left\lfloor \frac{B-1}{2} \right\rfloor) \\
&\geq \frac{1}{G(j)} \sum_{n_1+n_2+\dots+n_K \leq \left\lfloor \frac{B-1}{2} \right\rfloor} \prod_{k=1}^{k=K} \frac{\rho_{k,V}(j)^{n_k}}{n_k!} \quad (15)
\end{aligned}$$

For a single-class of calls

$$P_{Acc} \geq \frac{1}{G(j)} \sum_{i=0}^{i=\left\lfloor \frac{B-1}{2} \right\rfloor} \frac{\rho_{1,V}(j)^i}{i!} \quad (16)$$

Multi-hop case: Consider the attempt to setup an $(M-1)$ -hop call ($M \geq 3$) along the nodes (p_1, \dots, p_M) . The probability of call acceptance is given by Equation (9). From Equation (9) and Lemma 2

$$\begin{aligned}
P_{Acc} &\geq P(\text{Number of calls in } R(p_1) \leq \left\lfloor \frac{B-1}{2} \right\rfloor) \times \\
&P(\text{Number of calls in } R'(p_2) \leq \left\lfloor \frac{B-2}{2} \right\rfloor) \times \\
&P(\text{Number of calls in } R''(p_3) \leq \left\lfloor \frac{B-3}{2} \right\rfloor) \times \\
&\dots \\
&P(\text{Number of calls in } R''(p_{M-1}) \leq \left\lfloor \frac{B-3}{2} \right\rfloor)
\end{aligned}$$

$$\begin{aligned}
P_{Acc} &\geq \frac{1}{G(p_1)} \sum_{n_1+n_2+\dots+n_K \leq \lfloor \frac{B-1}{2} \rfloor} \prod_{k=1}^{k=K} \frac{\rho_k(p_1)^{n_k}}{n_k!} \times \\
&\frac{1}{G'(p_2)} \sum_{n_1+n_2+\dots+n_K \leq \lfloor \frac{B-2}{2} \rfloor} \prod_{k=1}^{k=K} \frac{\rho_k(p_2)^{n_k}}{n_k!} \times \\
&\dots \\
&\frac{1}{G''(p_{M-2})} \sum_{n_1+n_2+\dots+n_K \leq \lfloor \frac{B-3}{2} \rfloor} \prod_{k=1}^{k=K} \frac{\rho_k(p_{M-2})^{n_k}}{n_k!} \times \\
&\frac{1}{G'''(p_{M-1})} \sum_{n_1+n_2+\dots+n_K \leq \lfloor \frac{B-3}{2} \rfloor} \prod_{k=1}^{k=K} \frac{\rho_k(p_{M-1})^{n_k}}{n_k!} \quad (17)
\end{aligned}$$

where $G'(j) = \sum_{0 \leq n_1+\dots+n_K \leq B-1} \prod_{k=1}^{k=K} \frac{\rho_k(j)^{n_k}}{n_k!}$ and

$$G''(j) = \sum_{0 \leq n_1+\dots+n_K \leq B-2} \prod_{k=1}^{k=K} \frac{\rho_k(j)^{n_k}}{n_k!}.$$

For the single-class case:

$$\begin{aligned}
P_{Acc} &\geq \frac{1}{G(p_1)} \sum_{i=0}^{i=\lfloor \frac{B-1}{2} \rfloor} \frac{\rho_1(p_1)^i}{i!} \times \\
&\frac{1}{G'(p_2)} \sum_{i=0}^{i=\lfloor \frac{B-2}{2} \rfloor} \frac{\rho_1(p_2)^i}{i!} \times \\
&\dots \\
&\frac{1}{G''(p_{M-2})} \sum_{i=0}^{i=\lfloor \frac{B-3}{2} \rfloor} \frac{\rho_1(p_{M-2})^i}{i!} \times \\
&\frac{1}{G'''(p_{M-1})} \sum_{i=0}^{i=\lfloor \frac{B-3}{2} \rfloor} \frac{\rho_1(p_{M-1})^i}{i!} \quad (18)
\end{aligned}$$

Using the same approximations as in Equations (12) and (13), we can determine the minimum value of the acceptance probability P_{Acc}^{Min} :

$$P_{Acc}^{Min} = \frac{1}{G} \sum_{i=0}^{i=\lfloor \frac{B-1}{2} \rfloor} \frac{\rho^{Min i}}{i!} \quad \text{for single - hop calls (19)}$$

$$\begin{aligned}
P_{Acc}^{Min} &= \left[\frac{1}{G} \sum_{i=0}^{i=\lfloor \frac{B-1}{2} \rfloor} \frac{\rho^{Min i}}{i!} \right] \times \left[\frac{1}{G'} \sum_{i=0}^{i=\lfloor \frac{B-2}{2} \rfloor} \frac{\rho^{Min i}}{i!} \right] \times \\
&\left[\frac{1}{G''} \sum_{i=0}^{i=\lfloor \frac{B-3}{2} \rfloor} \frac{\rho^{Min i}}{i!} \right]^{M-3} \quad \text{for multihop calls (20)}
\end{aligned}$$

where $G = \sum_{i=0}^{i=B} \frac{\rho^{Max i}}{i!}$, $G' = \sum_{i=0}^{i=B-1} \frac{\rho^{Max i}}{i!}$, and

$$G'' = \sum_{i=0}^{i=B-2} \frac{\rho^{Max i}}{i!}.$$

3.2.2 System Saturation Probability

For the case of a single-class of calls, the probability that the network is saturated *i.e.*, no further calls can be accepted is given by P_{Sat} . If the number of type-V calls in a region is B , then this

would require at least B slots to be used, and no further calls can be accepted.

$$P(\text{Saturation in } R(j)) = P(B \text{ slots are used})$$

$$\begin{aligned}
P(\text{Saturation in } R(j)) &\geq P(\text{Number of type - V calls at } R(j) = B) \\
&\geq \frac{1}{H(j)} \frac{\rho_{1,V}(j)^B}{B!} \quad (21)
\end{aligned}$$

$$P_{Sat} \geq \prod_{i=1}^{i=N} \frac{1}{H(i)} \frac{\rho_{1,V}(i)^B}{B!} \quad (22)$$

$$P_{Sat} \geq \left[\frac{1}{H} \frac{\rho_{1,V}^{Max B}}{B!} \right]^N \quad (23)$$

3.2.3 A Summary of the Results

- The Equations (19), (20), (12), and (13) suggest that the call acceptance decreases with system load, this decrease being rapid at high loads.
- For an incoming call's chances of acceptance to be maximized, Equations (7) and (10) suggest that the minimum $\rho(j)$ across the network be maximized: this suggests that load-balancing would help improve the acceptance rate.
- If all the nodes are within the transmission range of one another (all communication is single-hop), then the upper and lower bounds (Equations (19) and (12)) converge with $\rho_k(j) = N \frac{\lambda_k}{\mu_k}$.
- To ensure that the call acceptance is always above a certain threshold irrespective of the load, Equations (19) and (20) indicate that the network must be well-provisioned *i.e.*, B must be sufficiently high.
- As boundary cases, the following are seen to hold for the call acceptance rates: as the number of slots increases, it tends to unity. As the call duration increases, it approaches zero.

3.2.4 The Case of Preemption

The analysis so far has been done under the assumption that high-priority calls cannot preempt lower-priority ones. However, a realistic scenario may require that high-priority calls are ensured high probability of call acceptance. This may require introduction of preemption into the system. The analysis of the steady-state probabilities of a preemptive Markov process is a difficult problem. The stationary distribution of the highest priority calls can be easily obtained since these calls effectively ignore the presence of other low-priority calls. Thus, the stationary distribution of the class-1 calls is the same as that of the single-class system given in Equations (19), (20), (12), and (13).

3.2.5 The Failure of Shortest-path Routing

The analysis tells us that the parameters: the call acceptance probability and the system saturation probability depend on the load on the network, the hopcount of the path, and the routing protocol. We first look at the performance of shortest-path routing relative to the theoretical guarantees. The routing protocol is related to the call acceptance and the system saturation probability through the factor $f_k(i, j)$ specified in Equation (1).

Shortest-path routing: Shortest-path routing computes the shortest path between the source and the destination where the distance




Figure 7: The normalized average fraction of calls being routed to a node with increasing distance from the center for shortest-path routing. The arrival rate is 0.04 calls per second at a node.




Figure 8: The normalized average fraction of calls being routed to a node with increasing distance from the center for shortest-path routing. The arrival rate is 1 calls per second at a node.

refers to the Euclidean distance between the source and the destination. In a highly dense network, the authors of [12] proved that the average path length obtained when shortest-path routing is employed is $0.905R$ where R is the radius of the network. This leads to heavier load at the center region of the network. We simulate shortest-path routing and measure the call acceptance rate. The Figures 7 and 8 indicate the loading of the center of the network, and decreasing load away from the center where the ring can be regarded as a unit of distance from the center (refer Section 4 for more details). The Figures 9, 10, and 11 show that the shortest-path routing has a call acceptance rate much below the theoretical limit. Note that even in Figure 9, the system has several calls with varying hops, which would be the case in a realistic scenario. The results shown in Figures 9, 10, and 11 are got by measuring the acceptances for single-hop, 2-hop, and 3-hop calls, respectively. The reason that shortest-path routing performs badly is due to the fact that a majority of the calls are routed through the center of the network resulting in a high load in the center. This problem suggests the use of load-balancing to alleviate the formation of hotspots and to increase the call acceptance.




Figure 9: Call acceptance probability of single-hop calls using shortest-path routing vs varying load.




Figure 10: Call acceptance probability of 2-hop calls using shortest-path routing vs varying load.

3.3 Load-balancing

We consider the following strategies for load-balancing:

- Ring-based routing: Ring-based routing [12] transfers the load from the center to the periphery of the network. The scheme makes use of heuristics to balance the load. We define the following terms:
 - The center node or center of a network, C , is the node for which,
$$\max_{\forall x}(HC(C, x)) \leq \min_{\forall y}(\max_{\forall z}(HC(y, z)))$$
for all nodes x, y , and z in the network. Here $HC(a, b)$ denotes the hopcount of the shortest path from node a to node b .
 - Each node in the network belongs to a *Ring* denoted by $Ring_i(r_i, r_{i+1})$. A *Ring* is an imaginary division of the network into concentric rings about the center of the network. The thickness of the ring is given by $r_{i+1} - r_i$. A node that belongs to $Ring_i$ lies at a distance in (r_i, r_{i+1}) from the center of the network.

The load balancing heuristic that we use is a Preferred Outer Ring routing Scheme (PORS) [12]. In this strategy, traffic




Figure 11: Call acceptance probability of 3-hop calls using shortest-path routing vs varying load.

generated in a node in $Ring_i$ and destined for a node in $Ring_j$ must not go beyond the rings enclosed by $Ring_i$ and $Ring_j$. Further, the packets must be preferentially routed through the outer of the two rings. Thus, for nodes belonging to the same ring, packets must be preferentially transferred in the same ring. For nodes belonging to different rings, all angular transmissions must preferentially take place in the outer of the two rings while the radial transmissions transfer packets across the rings. Thus, PORS affects the hopcount while at the same time moving most of the load away from the center.

- **Bandwidth-limited routing:** Bandwidth-limited routing is a more direct form of load-balancing that uses an estimate or measurement of the available bandwidth to select a path. It differs from the two previous methods (shortest-path routing and PORS) in that it is dynamic: constantly adapting to changes in the network state. There are two opposing metrics that such a scheme attempts to reconcile. It tries to choose paths with the highest available bandwidth. These paths, usually, tend to be longer than the shortest path. As a result, the available bandwidth of the path, which is the minimum of the available on the constituent links, is more likely to decrease. The scheme that we use is based on the Shortest-dist (P, n) studies in [13]. Shortest-dist (P, n) heuristic finds a path P with the shortest distance

$$dist(P, n) = \sum_{i=1}^k \frac{1}{r_i^n}$$

where r_1, \dots, r_k are the max-min fair rates of links on the path P with k hops. We use a variant of this heuristic. The weight for the link (u, v) is weighted by

$$\frac{1}{B(u, v)^n}$$

where $B(u, v)$ is the estimated bandwidth of the link, and n is a weighting factor. We simply estimate this as the minimum of the number of free slots at nodes u and v . The intuition behind this heuristic is that when the links are weighted thus, shortest-path routing will select a path that minimizes $\sum_{i=1}^k \frac{d_i}{B_i^n}$ where k is the number of hops, d_i is the Euclidean distance of the i th hop, and B_i is the estimated bandwidth of the link traversed on the i th hop. This heuristic tends

Table 1: Parameters used in the simulation

Parameter	Value
Number of nodes	50
Number of slots	32
Terrain area	1000 m × 1000 m
Transmission range	300 m
Average call duration	30 s
Simulation duration	200 s
Number of seeds	20




Figure 12: Variation of Call Acceptance vs ρ for Single-hop calls.

to select links with high available estimated bandwidth that would also form a short path to the destination. We set the exponent n to 1 for our experiments.

4. SIMULATION STUDIES

To study the actual behavior of the parameters of interest, we built an Ad hoc wireless network simulator in C++. The network is TDMA-based. Reservation involves two steps: finding a path using one of the routing protocols discussed and reserving slots along the path. Slot allocation for a particular call is done in a greedy manner. If at any intermediate node, the number of free slots is found to be inadequate, the call is rejected. Calls are generated at each node according to a Poisson process and the accepted calls have an exponentially distributed call duration. The nodes are not mobile. The parameters of the simulation are specified in Table 1. The simulations are run with 20 seeds: each run generates a random topology. In each run, calls are generated randomly according to a Poisson distribution with an exponentially distributed duration. We ran the simulations for a duration of 200s.

For the simulation studies, we vary the load by varying the call arrival rate at each node. We compare the call acceptance probabilities for varying values of the ratio $\rho = (\text{Average Call Arrival Rate} \times \text{Average Call Duration})$. In order to compare the theoretical values and the experimental results, we need to translate the ρ value to the $\rho_{1,v}^{Max}$ value. Thus, we also measure the average fraction of calls that pass through a region. This factor is an indication of the nature of the routing protocol used. We then measure the call acceptance of calls based on their hopcount for different routing protocols and compare with the theoretical limits. Results presented in this paper conform to 95% confidence intervals.




Figure 13: Variation of Call Acceptance vs ρ for 2-hop calls.




Figure 14: Variation of Call Acceptance vs ρ for 3-hop calls.

5. SIMULATION RESULTS

5.1 Call Acceptance Probability

We have compared the probability of call acceptance of shortest-path routing, Bandwidth-limited routing (BW), PORS, and the theoretical bounds at different values of load (in terms of the ratio ρ). We have also studied the acceptance probability for hopcount values of 1, 2, and 3 (Figures 12, 13, and 14). In all the results, the call acceptance probability value decreases with an increase in the network load, as expected. Further, the curves depicting the call acceptance probability values of shortest-path routing, BW, and PORS lie within the region surrounded by P_{Acc}^{Max} and P_{Acc}^{Min} .

PORS performs only marginally better than shortest-path routing (and in fact worse for single-hop calls) while BW performs significantly better. PORS attempts to load balance implicitly by routing calls to the periphery: this may not be the most effective strategy because nodes in one ring can interfere with those in the other rings. Also it does not take into account the fact that a longer path would result in more resources being consumed affecting the acceptance rate of calls in the future. This is probably the reason why the single-hop calls have a lower acceptance rate in PORS. BW, by using an explicit bandwidth-based load-balancing is evidently more effective. To bring out the difference in the performance of the three routing algorithms, we compute the fraction of all generated




Figure 15: The normalized average fraction of calls being routed to a node with increasing distance from the center. The arrival rate is 0.04 calls per second at a node.




Figure 16: The normalized average fraction of calls being routed to a node with increasing distance from the center. The arrival rate is 1 calls per second at a node.

calls that arrive at a node. We compute the average of this fraction for all nodes that belong to a ring and hence can be considered to be at a fixed distance from the center of the network. The Figures 15 and 16 plot this average fraction (normalized so that the least number is 1 and all the others are divided by this least number) for two different loads on the network. In both cases, shortest-path routing has a high load near the center. PORS shifts this load to the periphery but incurs the cost of higher path length. BW behaves like shortest-path when the network is lightly loaded but shifts the calls to the periphery with an increasing load.

The difference between the theoretical upper bound and the experimental results is partly the result of the approximations and assumptions used in our model. However, the difference also reflects the inadequacy of the existing protocols in load-balancing.

The increase in the call acceptance probability of the load-balancing schemes as compared to shortest-path routing indicates the importance of load-balancing in ensuring better throughput in terms of call acceptance. In fact, load-balancing seems to be an important method of approaching P_{Acc}^{Max} . The results indicate that an ideal load-balancing based routing protocol can come close to the theoretical upper bound.




Figure 17: Variation of Saturation Probability vs ρ .




Figure 18: Rank-based priority scheme.

5.2 System Saturation Probability

The variation of the probability of system saturation with load is shown in Figure 17. This metric remains near zero for moderate-to-heavy loads, and takes on an appreciable value only at high values of load. This indicates that system saturation is a rare occurrence for the common values of load. Thus, the network rarely enters a state where every new call is rejected. This also implies that for the common values of load, it is always possible to ensure that some fraction of the calls are guaranteed acceptance. This fraction is based on the values of the probability of call acceptance at that load.

5.3 Deterministic Guarantees

Our aim is to ensure that a certain number of calls in the network can be assured of acceptance. We can do so by pegging these calls at a high priority. Consider the following **rank-based priority scheme**: (Figure 18) Calls are prioritized according to the classes to which they belong. In addition, calls that belong to the highest priority are further allocated to sub-classes which are based on the address or ID of the source of the call. Further, call admission ensures that only one call of a given sub-class exists in the system. This implies that a particular node can originate only one such highest priority call. Preemption is permitted amongst the sub-classes themselves so that a high-priority sub-class has a better chance of acceptance. Hence a scenario can be envisaged as follows: the network is deployed in a military scenario in which the nodes are under the control of various communicating officers. The node ID can be assigned based on the rank of the officer using

the node. Calls are prioritized at the time of call admission into various classes. These calls then have probabilities of acceptance depending on the class to which they have been assigned and the network state. In addition, the calls of the highest priority class are assigned to sub-classes based on their node ID. Thus, to ensure that the call of the highest-ranking officer (say the General) always gets through, the general's node would be assigned a high-priority node ID. Thus, a set of nodes can be designated to ensure certain call acceptance. To ensure that these guarantees provided are effective, we need to estimate the number of calls (which is equivalent to the number of sub-classes) for which certain call acceptance can be ensured, and the call acceptance for the sub-classes which lie outside the former class.

5.3.1 Deterministic Guarantee Limit

The *Deterministic guarantee limit* D refers to the number of sub-classes of the highest priority class that can be ensured deterministic call acceptance as outlined at the beginning of this section. These sub-classes are referred to as the deterministic sub-classes. From

$$\begin{aligned} \text{Number of calls in } R(j) = x &\Rightarrow \\ \text{Number of used slots in } R(j) &\leq cx, \end{aligned} \quad (24)$$

if $x = \lfloor \frac{B}{c} \rfloor$, then the number of used slots in $R(j) \leq B$. If the total number of sub-classes in the network $= \lfloor \frac{B}{c} \rfloor$, then for every node j , the number of used slots in $R(j) \leq B$. Thus, this is the number of sub-classes that can be definitely accepted by every region of the network at a given time. By allocating a unique set of slots to each of the $\lfloor \frac{B}{c} \rfloor$ sub-classes, we can ensure that calls of these sub-classes are accepted (of course, any lower priority calls may need to be preempted in the process). Thus, the Deterministic guarantee limit $D \geq \lfloor \frac{B}{c} \rfloor$. This implies that $\lfloor \frac{B}{c} \rfloor$ sub-classes can be ensured deterministic call acceptance. However, this being a lower bound it may be possible for some more sub-classes to be ensured of this deterministic acceptance.

Independence of the Guarantee Limit and Mobility

At this point, we also would like to point out the effect of the mobility of the nodes on the limit. The deterministic guarantee limit is independent of the mobility. The set of sub-classes $\{1, \dots, \lfloor \frac{B}{c} \rfloor\}$ are ensured of deterministic acceptance even in the face of node mobility. Mobility in the network leads to path breaks and, subsequent, route reconfiguration attempts. In any such attempt, the calls belonging to the deterministic sub-classes retain their priority. Thus, these calls are guaranteed resources during the reconfiguration.

5.3.2 Probability of Acceptance for the Probabilistic Sub-classes

The sub-classes other than the deterministic sub-classes are referred to as the probabilistic sub-classes. Since sub-classes are assigned based on node IDs, there are N sub-classes, designated $\{1, \dots, N\}$ in decreasing order of priority. We are considering the call acceptance of a call belonging to a sub-class $n > \lfloor \frac{B}{c} \rfloor$ (all calls in any of the sub-classes $\{1, \dots, \lfloor \frac{B}{c} \rfloor\}$ are of a higher priority than this call and are within the deterministic guarantee limit) at a time t . We denote the probability that a call of sub-class i exists in the network at time t by $p_i(t)$. Let $q_i(t) = 1 - p_i(t)$.

Denote: the acceptance of call of sub-class n as ACC_n , and the number of calls \in sub-classes $\{1, \dots, n-1\}$ as $Count(1, n-1)$. As in Equation (24), if $Count(1, n-1)$ is less than $\lfloor \frac{B}{c} \rfloor$, then for

every node j , the number of slots used by calls of these sub-classes is $\leq B - c$. All the remaining c slots are either free or are used by lower-priority calls which can be preempted by the call belonging to sub-class n . Thus, the call of sub-class n can be accepted. Thus

$$\begin{aligned} \text{At time } t, \text{Count}(1, n-1) < \lfloor \frac{B}{c} \rfloor &\Rightarrow \\ \text{Call of sub-class } n \text{ is accepted} & \end{aligned}$$

$$P(\text{Call of sub-class } n \text{ is accepted} | \text{Count}(1, n-1) < \lfloor \frac{B}{c} \rfloor) = 1 \quad (25)$$

By denoting the probability of acceptance of the call belonging to sub-class n at time t as $P_n(t)$:

$$\begin{aligned} P_n(t) &= [P(\text{ACC}_n | \text{Count}(1, n-1) < \lfloor \frac{B}{c} \rfloor) \\ &\times P(\text{Count}(1, n-1) < \lfloor \frac{B}{c} \rfloor)] \\ &+ [P(\text{ACC}_n | \text{Count}(1, n-1) \geq \lfloor \frac{B}{c} \rfloor) \\ &\times P(\text{Count}(1, n-1) \geq \lfloor \frac{B}{c} \rfloor)] \quad (26) \end{aligned}$$

$$\begin{aligned} P_n(t) &\geq P(\text{Count}(1, n-1) < \lfloor \frac{B}{c} \rfloor) \\ P_n(t) &\geq \sum_{\substack{S \subseteq \{1, \dots, n-1\} \\ |S| \leq \lfloor \frac{B}{c} \rfloor}} \prod_{l \in S} p_l(t) \prod_{r \in \{1, \dots, n-1\} - S} q_r(t) \quad (27) \end{aligned}$$

When the calls at each node follow an identical probability distribution *i.e.*, $p_j(t) = p(t), \forall j \in \{1, \dots, N\}$, Equation (27) simplifies to

$$P_n(t) \geq \sum_{i=0}^{\lfloor \frac{B}{c} \rfloor} \binom{n-1}{i} p(t)^i q(t)^{n-i-1} \quad (28)$$

6. CONCLUSION

A realistic analysis of the nature of QoS guarantees is crucial in the design of new protocols and the improvement of existing ones to handle the growing diversity of demands on networks. In this paper, we have analyzed a TDMA-based Ad hoc wireless network. We have derived an upper bound on the probability of call acceptance: a bound that gives us a measure of the number of calls that can be allowed into the network, and a lower bound on the probability of system saturation: a number that indicates the likelihood of the network being unable to accept any further calls. Our analysis takes into consideration the behavior of the routing protocol and the inter-dependence of resources (time-slots) of neighboring regions in a wireless network. Further, our simulation studies indicate that the set of protocols tested fall short of the established bounds. Amongst the three protocols compared, the one that incorporated load-balancing out-performed the shortest-path routing based protocol. This clearly indicates the importance of load-balancing in the attainment of high network performance, and the provision of better QoS guarantees.

We have estimated the deterministic guarantee limit. This limit indicates that it is always possible to ensure QoS guarantees for a certain sub-class of calls irrespective of the mobility and resource constraints of the network.

When the nodes are moving, the number of nodes in a given region becomes time-dependent. This in turn is reflected in the factor ρ becoming time-independent. We are studying the effect of time-dependence of ρ on the call acceptance.

The experimental studies in this work were performed with a single-class of calls. The next step would involve studying the effect of introducing multiple classes of calls. Further, we are working on extending the analysis to handle the case of call preemption, and on obtaining tighter estimates. The modeling of the routing algorithm needs to be refined so that we can make predictions based on the $f_k(i, j)$ of different protocols. The experimental studies also need to be extended to compare other protocols to infer the essential and desirable properties of protocols that approach optimal-behavior.

7. REFERENCES

- [1] P. Gupta and P. R. Kumar, "The Capacity of Wireless Networks", *IEEE Transactions on Information Theory*, vol. 46, no. 2, pp. 388-404, March 2000.
- [2] P. Gupta and P. R. Kumar, "Towards an Information Theory of Large Networks: An Achievable Rate Region", *IEEE Transactions on Information Theory*, vol 49, no. 8, pp. 1877-1894, August 2003.
- [3] M. Grossglauser and D. N. C. Tse, "Mobility Increases the Capacity of Ad hoc Wireless Networks", *IEEE/ACM Transactions on Networking*, vol. 10, no. 4, pp. 477-486, August 2002.
- [4] U. C. Kozat and L. Tassiulas, "Throughput capacity of Random Ad hoc Networks with Infrastructure Support", in *proceedings of ACM MOBICOM 2003*, pp. 55-65, September 2003.
- [5] T. Bheemarajuna Reddy, I. Karthigeyan, B. S. Manoj, and C. Siva Ram Murthy, "Quality of Service Provisioning in Ad hoc Wireless Networks: A Survey of Issues and Solutions", to appear in *Ad Hoc Networks Journal*.
- [6] P. Sinha, R. Sivakumar, and V. Bharghavan, "CEDAR: A Core-Extraction Distributed Ad hoc Routing Algorithm", *IEEE Journal on Selected Areas in Communications*, vol. 17, no. 8, pp. 1454-1465, August 1999.
- [7] W. Liao, Y. Tseng, and K. Shih, "A TDMA-based Bandwidth Reservation Protocol for QoS Routing in a Wireless Mobile Ad hoc Network", in *proceedings of IEEE ICC 2002*, vol. 5, pp. 3186-3190, May 2002.
- [8] G. Barua and I. Chakraborty, "Adaptive Routing for Ad hoc Wireless Networks Providing QoS Guarantees", in *proceedings of IEEE ICPWC 2002*, pp. 196-200, December 2002.
- [9] John G. Kemeny and J. L. Snell, *Finite Markov Chains*, Van Nostrand, New York, 1960.
- [10] P. Buchholz, G. Ciardo, P. Kemper, and S. Donatelli, "Complexity of Memory-efficient Kronecker Operations with Applications to the Solution of Markov Models", *INFORMS Journal on Computing*, vol. 12, no. 3, pp. 203-222, July 2000.
- [11] D. Bertsekas and R. Gallager, *Data Networks*, Prentice-Hall, New Jersey, 1992.
- [12] G. Bhaya, B. S. Manoj, and C. Siva Ram Murthy, "Ring-Based Routing Schemes for Load Distribution and Throughput Improvement in Multi-hop Cellular, Ad hoc, and Mesh Networks", in *proceedings of HiPC 2003*, LNCS 2913, pp. 152-161, December 2003.
- [13] Qingming Ma, Peter Steenkiste, and Hui Zhang, "Routing High-bandwidth Traffic in Max-min Fair Share Networks", in *proceedings of ACM SIGCOMM*, pp. 206-217, August 1996.